

## PTC38

### Water based fluoropolymer lubricant coating



FEATURES	<ul style="list-style-type: none"> <li>✓ Water based coating</li> <li>✓ Clean dry film</li> <li>✓ Remains flexible over a wide range of temperatures</li> <li>✓ Good release properties with a low coefficient of friction</li> </ul>								
BENEFITS	<ul style="list-style-type: none"> <li>✓ Dry lubrication</li> <li>✓ No soil or grease</li> <li>✓ Compliant to RoHS and REACH</li> <li>✓ Exceptional Non-Stick</li> <li>✓ Facilitates assembly with robots</li> </ul>								
APPLICATIONS	<ul style="list-style-type: none"> <li>✓ O-Rings</li> <li>✓ Elastomeric Gaskets</li> <li>✓ Flexible Diaphragms</li> </ul>								
PROPERTIES (Liquid TYPE, not cured)	<table> <tr> <td>Color:</td> <td>White</td> </tr> <tr> <td>Pigment:</td> <td>PTFE</td> </tr> <tr> <td>Binder:</td> <td>Thermoset Resin</td> </tr> <tr> <td>Carrier:</td> <td>Water</td> </tr> </table>	Color:	White	Pigment:	PTFE	Binder:	Thermoset Resin	Carrier:	Water
Color:	White								
Pigment:	PTFE								
Binder:	Thermoset Resin								
Carrier:	Water								
PROPERTIES (as cured)	<table> <tr> <td>Color:</td> <td>Transparent white</td> </tr> <tr> <td>Service temperature -continuous:</td> <td>155°C (310°F)</td> </tr> </table>	Color:	Transparent white	Service temperature -continuous:	155°C (310°F)				
Color:	Transparent white								
Service temperature -continuous:	155°C (310°F)								

\* Property values in typical specification are provided as general information only. They are not final production specification.